

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

1306 Air cylinder complete

Air Cylinder w/ closing valve. 1,45 liter (50 fl oz). Work pressure 300bars/4350psi



1307 Air cylinder US complete

Air Cylinder w/ closing valve. 1,45 liter (50 fl oz), certified for the US and Canadian market. Work pressure 200bars/2900psi



1308 Adapter 200/300 bar (Yoke-DIN477)

Adapter for filling of the air cylinder from Yoke 200 bars (2900psi) standard.



1309 Closing valve w/ manometer 1310 Air filling hose w/ connections

Air filling hose with couplings and pressure releaser.





Utskrevet av Espen Marthinussen 02.01.2012 09:16:41.

Side 1 av 13





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

2104 End plug for projectiles with internal line

End plug for Projectile Rescue 230 (art no 2101), Projectile PLT 125 (art no 3101) and Projectile PLT Mini 100 (art no 4101). The projectile must never be fired without the end plug.



2105 Line 2mm hollow braided Dyneema

Safety Line for Art No 2101 or 4101, 2mm.

Comes on a spool of 350 meters. Breaking strength 7800N.



4000 PLT Mini complete

Contents:

1 art no 4020 PLT Mini Launching unit

1 art no 4006 CO2 cartridge 4-pack

2 art no 4101 Projectile PLT Mini 100

1 art no 4102 Projectile PLT Mini-rubber

1 art no 4200 Loading device

1 art no 4202 Linebox PLT Mini 2mm nylon

1 Digital and soft copy User Manual

Typical shooting range with a dry and clean line of 2mm (Art No 4110) and Projectile PLT Mini 100 art

no 4101: 100m.

Typical shooting range with a dry and clean line of 2mm (Art No 4110) and Projectile PLT Mini-rubber art

no 4102 : 90m.

Breaking strength: 190kg

The PLT Mini is a light version shoulder launched

PLT.



Utskrevet av Espen Marthinussen 02.01.2012 09:16:41.

Side 2 av 13





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

4000U PLT Mini complete without CO2

The PLT Mini is a light version shoulder launched PLT. This is the standard package which is the same as Art No 4000, without CO2.



4006 CO2 cartridge, 4-pack

Disposable 33 gram CO2 cartridges. Comes in a 4-pack. Note that these can be shipped by Air as dangerous goods.



4020 PLT Mini Launching Unit

The PLT Mini can be used either with CO2 cartridges (art no 4006) or by compressed air. The shooting length will be app the same.



4021 PLT Mini Launching Unit Black

Same as art no 4020, but in black version.



4060 PLT Mini Complete Rescue Pack

Contents

1 art no 4020 PLT Mini Launching unit

5 art no 4006 CO2 cartridge 4-pack

2 art no 4101 Projectile PLT Mini 100

1 art no 4102 Projectile PLT Mini-rubber

1 art no 4104 Lightstick (5-pack)

1 art no 4200 Loading device

2 art no 4202 Linebox PLT Mini 2mm nylon

1 Digital and soft copy User Manual

Typical shooting range with a dry and clean line of



Utskrevet av Espen Marthinussen 02.01.2012 09:16:42.

Side 3 av 13

Postadresse/mailadress Restech Norway as P.O.Box 624 N-8008 Bodø Norway Kontoradresse/Officeadress Restech Norway as Olav V gt 112 N-8004 Bodø Norway

Phone: +47 7554 2440
Fax: +47 7554 2441
Mail: restech@restech.no
www.restech.no





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

2mm (Art No 4110) and Projectile PLT Mini 100 art

no 4101: 100m.

Typical shooting range with a dry and clean line of 2mm (Art No 4110) and Projectile PLT Mini-rubber art

no 4102:90m.

Breaking strength: 190kg

The PLT Mini is a light version shoulder launched

PLT.

4100 Storage container PLT Mini

Water proof container in heavy duty plastic. Easy storage and easy handling. Air and water tight. It even floats in the water. Internal dim. 580x440x220 mm, External dim. 650x510x242mm. 56liter and 8,5kg. Colour orange.



4101 Projectile PLT Mini 100

Projectile PLT Mini made from ABS and aluminum inner tube. Filled with an internal line of 110m (120yd). The projectile floats.

Typical shooting range with a dry and clean line of

2mm (Art No 4110): 100m. Breaking strength : 190kg



4102 Projectile PLT Mini-rubber

Soft projectile made from Polyurethan. Used for general line transfer and training. A lightstick can easily be attached for visibility at night. Must be used with an external line or Linebox Art no 4202 . Typical shooting range with a dry and clean line of

2mm (Art No 4110): 90m. Breaking strength: 190kg



Utskrevet av Espen Marthinussen 02.01.2012 09:16:42.

Side 4 av 13

Phone: +47 7554 2440
Fax: +47 7554 2441
Mail: restech@restech.no
www.restech.no





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

4103 Projectile PLT Mini-sharp graple

Graple with sharp ends for pick-up. Made from POM and Stainless Steel. The projectile does not float. Typical used with an external line or Linebox Art 4202. Typical shooting range with a dry and clean line of 2mm (Art No 4110): 75m. Breaking strength: 190kg



4104 Lightstick for projectile PLT Mini-rubber 5 pcs

Lighsticks for art no 4102. Provides visibility during night time. Green colour with 6 hours burning time. Comes in 5-pack.



4105 Projectile PLT/Mini-Rescue bouy

Projectile that contains an automatic inflatable life buoy. Will inflate within 2 sec. after entering the water. Can be used with PLT and PLT Mini. The inflator has an expiry date. Uses 33gram CO2 cartridge.

Typical shooting range with a dry and clean line of 2mm (Art No 4110) with the PLT Mini: 80m.

Breaking strength: 190kg

Typical shooting range with a dry and clean line of 3,2mm(Art No 2103) with the PLT: 115m.

Breaking strength: 200kg



4106 Projectile PLT Mini-rubber tip

Rubber tipped plastic projectile that floats. Used for general line transfer or as a training projectile for PLT Mini.

Typical shooting range with a dry and clean line of 2mm (Art No 4110) with the PLT Mini: 95m.

Breaking strength: 190kg



Utskrevet av Espen Marthinussen 02.01.2012 09:16:43.

Side 5 av 13





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

4110 Safety line PLT Mini projectiles

Safety line for all PLT Mini projectiles, 2mm and 120m. Breaking strength 190kg.



4111 Packings and O-rings PLT Mini Launching unit

Packings and O-rings for PLT Mini.



4113 Projectile-entering graple 4

Titanium graple with black plastic coating. For entering constructions. For more information ask for brochure, "Entering solutions".



4114 Projectile PLT Mini-line pick-up graple

Closed graple for line pick-up. The closed ends secures the line within the barbes. Made from Stainless Steel and plastic.

Typical shooting range with a dry and clean line of 2mm (Art No 4110) with the PLT Mini: 75m. Breaking strength: 190kg



4115 Projectile-entering graple 3

Titanium graple with 3 tines that are barbed from centre to the tip. One tine can hold 2000kg at the centre and 350kg at the tip before bending. Black plastic coating. For entering constructions. Fits lines up to 9mm for direct climbing after launching. Can be used by PLT and PLT Mini Launching Unit.

Typical shooting range with a dry and clean double



Utskrevet av Espen Marthinussen 02.01.2012 09:16:43.

Side 6 av 13

Phone: +47 7554 2440
Fax: +47 7554 2441
Mail: restech@restech.no

www.restech.no





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

line of 3,2mm (Art No 2103) by PLT: 64m
Typical shooting range with a dry and clean double
line of 3,2mm (Art No 2103) by PLT Mini: 29m
Using 9mm Technora fibers single line and PLT: 37m
Using 9mm Technora fibers single line and PLT Mini:

4200 Loading device projectile PLT Mini 100

Loading device for reloading the 2mm (Art No 4110) line into art no 4101 and art no 4202. Connect to compressed air 5-10bars (72-145psi).



4202 Linebox 2mm-nylon line

Linebox containing safety line (min 90m of art no 4110). Reloads using loading device Art no 4200. Breaking strength: 190kg



4207 Quick coupling

Quick coupling for using the PLT Mini with compressed air. Fits any standard 5/8" diving cylinder. Reduces the pressure to the correct air pressure. Includes safety valve. With our air cylinder art no 1306/1307, you will get more than 35 shots.



Utskrevet av Espen Marthinussen 02.01.2012 09:16:43.

Side 7 av 13



Art No



Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

4303 Launching Tube PLT Mini

Launching Tube for PLT Mini.

Name and description




7032 Repacking set Life buoy w/ CO2

Repacking set for life buoy Art No 7035 and Art No 4105. Includes inflator, strips and a 33gram CO2 cartridge. The inflator has an expiry date.



7034 Repacking set Life buoy without CO2

Repacking set for life buoy Art No 7035 and Art No 4105. Includes inflator and strips. The inflator has an expiry date.



7035 Rescue Egg

Rescue Egg containing an automatically inflatable life buoy. No line attached. Ideal for MOB when ship is moving. The cover acts as a sea anchor. The inflator has an expiry date. Uses 33gram CO2 cartridge.



7036 Inflator for Rescue bouy

The inflator has an expiry date. The inflator is for the art no 4105, 7035 and repacking set for life buoys..



Utskrevet av Espen Marthinussen 02.01.2012 09:16:44.

Side 8 av 13





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

7038 Quick link ladder connector

Minimum order amount 2. Using the optional Ladder Connector the spacing remains the same when joining two ladders (order 2 for the Single Rung Ladder or order 3 for the Double Rung Ladder).

CE-EN 362.

7039 Ladder Single Rung 10m

10m, lightweight, noiseless, non conducting, contains no metal parts and presents no radar signal.

Built for heavy duty military use in marine environment!

One end of the ladder has a single attachment point for fast and easy deployment. The other end has a two separate attachment points. You can use this side to put 2 ladders together (with the optional Ladder Connectors) or you can use this side to connect it to two separate anchor points to rig it slightly more stable. Single Rung 200mm width. Rung spacing: 30cm. Using the optional Ladder Connector (art no 7038) the spacing remains the same when joining two ladders (order 2 for the Single Rung Ladder).



7040 Ladder Single Rung 15m

15m, specifications same as art no 7039.

Utskrevet av Espen Marthinussen 02.01.2012 09:16:44.

Side 9 av 13





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

7041 Ladder Single Rung 20m

20m, specifications same as art no 7039.

7042 Ladder Double Rung 15m

15m, lightweight, noiseless, non conducting, contains no metal parts and presents no radar signal. Built for heavy duty military use in marine environment! One end of the ladder has a single attachment point for fast and easy deployment. The other end has a two separate attachment points. You can use this side to put 2 ladders together (with the optional TAGS Ladder Connectors) or you can use this side to connect it to two separate anchor points to rig it slightly more stable. Double Rung 390mm width. Rung spacing: 30cm. Using the optional Ladder Connector (art no 7038) the spacing remains the same when joining two ladders (order 3 for the Double Rung Ladder). The double rung version is faster, more stable and more comfortable to climb than the single rung version. Especially in situations where you must climb downwards.



7043 Ladder Double Rung 20m

20m, specifications same as art no 7042.

8000 Whale Tagger complete

Whale tagger launcher:

Includes:

1 art no 1308 Filling adapter

1 art no 1306 Air cylinder with closing valve

2 art no 1303 Launching tube

1 art no 9400 Storage container

1 Red Dot aiming device

1 Shoulder support with quick connection

1 Base unit complete with valves and gauge.



Utskrevet av Espen Marthinussen 02.01.2012 09:16:51.

Side 10 av 13

Phone: +47 7554 2440
Fax: +47 7554 2441
Mail: restech@restech.no
www.restech.no





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

9001 Turbo oil 165 ml ,PRF 290/220

Lubricant, for keeping the line thrower in clean and in good working condition. Used ones a month. Acid and water free.



9002 Manometer w/ packing

Spare manometer with packing for the air cylinder.



9200 Storage container PLT 75/150 complete

Water proof container in heavy duty plastic. Easy storage and easy handling. Fits PLT 75 and 150 models. There are wheels on the container for easy transportation. Air and water tight. It even floats in the water. Internal dim. 580x440x330 mm, External dim. 670x510x372mm. 84liter and 14kg. Colour orange.



9300 Storage container PLT 125 complete

Water proof container in heavy duty plastic. Easy storage and easy handling. Fits PLT 125 model. There are wheels on the container for easy transportation. Air and water tight. It even floats in the water. Internal dim. 765x485x305 mm, External dim. 860x560x330mm. 113liter and 16,5kg. Colour orange.



Utskrevet av Espen Marthinussen 02.01.2012 09:16:52.

Side 11 av 13





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

9400 Storage container PLT Rescue 230 complete Water

for easy transportation. Colour black.

proof container in heavy duty plastic. Easy storage and easy handling. It even floats in the water. Fits PLT Rescue 230 complete. Internal dim. 1350x350x135 mm, External dim. 1410x415x159mm. 63,7liter and 12kg. There are wheels on the container



9401 Storage container PLT Mini, 75, 125 and 150

Water proof container in heavy duty plastic. Easy storage and easy handling. It even floats in the water. Fits PLT Mini, 75, R125 and 150 complete. Internal dim. 939x352x137 mm, External dim. 989x415x157mm. 45liter and 8kg. There are wheels on the container for easy transportation. Colour black.



9500 Storage container deep

Water proof container in heavy Duty plastic. Easy storage and easy handling. It even floats in the water. Internal dim. 1350x350x272 mm, External dim. 1410x415x296mm. 128,5liter and 16kg. There are wheels on the container for easy transportation. Colour black.



9900 Bauer Kompressoren PE100-TE 3 phase

100l/min, 400V 50Hz. Delivery time is 3 weeks from ordering. 230V or 60Hz can be ordered with a delivery time of 6 weeks. The price will increase by NOK 1000,-. Dimensions is 89x50x49cm and 40kg.



Utskrevet av Espen Marthinussen 02.01.2012 09:16:53.

Side 12 av 13





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No Name and description

9901 Bauer Kompressoren PE100-TW Single phase

100l/min, 400V 50Hz. Delivery time is 3 weeks from ordering. 230V or 60Hz can be ordered with a delivery time of 6 weeks. The price will increase by NOK 1000,-. Dimensions is 89x50x49cm and 40kg.



9902 Bauer Kompressoren PE100-TB 4-stroke petrol

100l/min, 4,2 kW, 5,7 Hp. Delivery time is app 2 weeks from ordering. Dimensions is 89x50x49cm and 42kg.



9903 Bauer Kompressoren Junior II, 3 phase

Compact Line Junior II 100l/min, 400V 60Hz. 230V is an option. Delivery time is 1-3 weeks from ordering. Dimensions is 66x36x42cm and 46kg.



Utskrevet av Espen Marthinussen 02.01.2012 09:16:53.

Side 13 av 13

